

DESCRIPTION: Rhino Linings® Polyurethane/Polyurea Pigment dispersions consist of organic and inorganic colorants dispersed in an engineered vehicle that is fully compatible with all Rhino Linings spray elastomer resin compounds.

TYPICAL USES: These can be used for coloring Spray, Cast Molded Components, Sports Surfaces, Roofing & Flooring, Military Camouflage, Medical & Prosthetics, Safety Wear, Molds & Tool Making, Pipeline Coatings, Motor-homes, Boats, Trucks & Buses, Automobiles, Shoe Soles, Foam Bedding, Sports Equipment, Machine Housings and Display Signage.

FEATURES & BENEFITS:

- Available in a variety of colors
- Good Compatibility with all Rhino Elastomer Systems
- Very low moisture content and will not contribute to foaming
- Homogeneous coloring of the system

MIXING INSTRUCTIONS:

- In 2 to 1 systems add 80 grams per gallon of liquid in the container.
- In 1 to 1 systems add 120 grams per gallon of liquid in the container.

When adding Rhino Linings pigments to a drum or other container constant agitation should be used to prevent the pigment from settling to the bottom of the container. Also the container should be agitated 1 minute for every gallon daily to prevent settling.

SAFETY PRECAUTIONS: Health Considerations - Consult the Rhino Linings® Safety Data Sheets (SDS)

This chemical system requires the use of proper safety equipment and procedures. Please follow the Rhino Linings® product SDS and Safety Manual for detailed information and handling guidelines.

For Your Protection: The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning the products and their uses, applications, storage and handling are only the opinion of Rhino Linings Corporation. Users should conduct their own tests to determine the suitability of these products for their own particular purposes and of the storage and handling methods herein suggested. The toxicity and risk characteristics of products made by Rhino Linings Corporation will necessarily differ from the toxicity and risk characteristics developed when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors.

Because of numerous factors affecting results, **Rhino Linings Corporation makes no warranty of any kind, express or implied**, other than that the material conforms to its applicable current Standard Specifications. Rhino Linings Corporation hereby disclaims any and all other warranties, including but not limited to those of merchantability or fitness for a particular purpose. No statements made herein may be construed as a representation or warranty. The liability of Rhino Linings Corporation for any claims arising from or sounding in breach of warranty, negligence, strict liability, or otherwise shall be limited to the purchase price of the material.

©2015 Rhino Linings Corporation. All rights reserved.