



# Shark Grip Data Sheet

Part # SG

**DESCRIPTION:** Shark Grip slip-resistant additive is a micronized polymer for addition to Concrete Solutions® coatings for slip resistance, fine texturing, and gloss reduction. Due to its low oil absorption and high solvent resistance, it will stir easily into most oil-based and latex-based paints and other coatings with minimal effect on the coating's viscosity. Its low density allows it to stay well suspended in thin materials such as stains. Shark Grip works best with solvent based and water based acrylic products.

**TYPICAL USES:** Shark Grip is a slip resistant additive that can be added to most clear or colored sealers to provide extra slip resistance.

**FEATURES & BENEFITS:**

- Can be added to paints, stains, and sealers
- Add to latex-based, oil-based and epoxy coatings
- Spherical-shaped particles allow easy cleaning of the surface
- Spherical-shaped particles provide a smoother feel under foot when used on pool decks and patios
- Slip resistance
- Easy addition into paints and stains
- Good chemical and abrasion resistance
- Good universal compatibility without viscosity effects

**CHEMICAL PROPERTIES:**

**Result**

Coverage Rate	1000 sqft per bottle
---------------	----------------------

**MIXING INSTRUCTIONS:** One bottle mixes with five gallons of sealer.

**NOT RECOMMENDED FOR:** Not for use on wood stains.

**HOW SUPPLIED:** 1 lb container

**SAFETY PRECAUTIONS: Health Considerations: Consult the Rhino Linings® Safety Data Sheets (SDS)**

Chemical systems require the use of proper safety equipment and procedures. Please follow the Rhino Linings® product SDS and Safety Manual for detailed information and handling guidelines.

**For Your Protection:** The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning the products and their uses, applications, storage and handling are only the opinion of Rhino Linings Corporation. Users should conduct their own tests to determine the suitability of these products for their own particular purposes and of the storage and handling methods herein suggested. The toxicity and risk characteristics of products made by Rhino Linings Corporation will necessarily differ from the toxicity and risk characteristics developed when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors.

Because of numerous factors affecting results, **Rhino Linings Corporation makes no warranty of any kind, express or implied**, other than that the material conforms to its applicable current Standard Specifications. Rhino Linings Corporation hereby disclaims any and all other warranties, including but not limited to those of merchantability or fitness for a particular purpose. No statements made herein may be construed as a representation or warranty. The liability of Rhino Linings Corporation for any claims arising from or sounding in breach of warranty, negligence, strict liability, or otherwise shall be limited to the purchase price of the material.

©2014 Rhino Linings Corporation. All rights reserved.

**Rhino Linings Corporation**

9747 Businesspark Avenue, San Diego, CA 92131  
858-450-0441 • Fax 858-450-6881  
1-800-422-2603  
www.rhinolinings.com

**Concrete Solutions by Rhino Linings**

7455 Carroll Road, San Diego, CA 92121  
1-800-232-8311 • Fax 858-566-4346  
www.concretesolutions.com