

PRODUCT NAME(S): HiChem™ 21-70-90 Resin

SECTION 1 – IDENTIFICATION

Manufacturer's Info:
Rhino Linings Corporation
9747 Businesspark Avenue
San Diego, CA92131

Product name: HiChem™ 21-70-90 Resin

Information phone: (858) 450 0441
Emergency contact: CHEMTREC (800) 424 9300

SECTION 2 – HAZARD(S) IDENTIFICATION

OSHA Hazard Communication Standard:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

GHS-Label Elements: **Signal Word:** **Pictogram(s):**
WARNING



GHS 08

Classification of the substance or mixture:

Hazard Class	Category	Hazard Statement Codes	Hazard Statements
Skin corrosion/irritation	3	H316	Causes mild skin irritation
Serious eye damage/Eye irritation	2B	H320	Causes eye irritation
Carcinogenicity	2	H351	Suspected of causing cancer by inhalation
Specific target organ toxicity, repeated exposure	2	H373	May cause damage to kidney and central nervous system through prolonged or repeated exposure May cause damage to lungs/respiratory system through prolonged or repeated exposure by inhalation

Precautionary Statements:

Prevention:	P201 P202 P281 P260 P264	Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe mist, vapors, spray. Wash exposed area with plenty of water and soap thoroughly after handling.
Response:	P332 + P313 P305 + P351 + P338 P337 + P313 P308 + P313	If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
Storage:	P405	Store locked up.
Disposal:	P501	Dispose of contents/container to hazardous or special waste collection point in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: Not known.

Note: Negative effects of the component classified as possible carcinogen to humans are minimized since it is dispersed in a liquid as opposed to an inhalable fine powder form. However, precautions should be taken to avoid breathing mists created by heating, mixing or spraying and dust from cutting or grinding of cured product containing this component.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS #	EC #	Concentration, %
Natural Oil Based Polyol	Trade Secret	Trade Secret	60 – 80
Glycol	Trade Secret	Trade Secret	1 – 10
Polyether Polyol	Trade Secret	Trade Secret	1 – 10
Titanium Dioxide	13463-67-7	236-675-5	1 – 10
Diethyltoluenediamine	68479-98-1	270-877-4	1 – 5
Zeolites	1318-02-1	930-915-9	1 – 5

SECTION 4 – FIRST-AID MEASURES

Description of First Aid measures:

Inhalation: Move to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory problems, seek medical attention.

Skin: Wash material off of the skin with plenty of soap and water. Remove contaminated clothing and shoes and wash them before reuse. Get medical advice/attention if irritation persists.

Eye: Rinse cautiously with water for several minutes, especially under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Do not rub eyes in order to prevent corneal injury. Get medical advice/attention if eye irritation persists.

Ingestion: Move to fresh air and keep at rest in a position comfortable for breathing. Remove dentures if any. Rinse mouth thoroughly with water and then drink 60 to 240 mL (2 to 8 oz). Get medical advice/attention if symptoms occur.

Most important symptoms/effects, acute and delayed: See Section 11 for more details.

General advice for First Aid responders: Show this SDS to physician.

Note to physician: Specific antidotes or neutralizers do not exist. Treatment should be supportive and based on the judgment of the physician in response to the reaction of the patient. Recommended medical monitoring for at least 24 hours.

SECTION 5 – FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray, alcohol-resistant foam, dry chemical or carbon dioxide fire extinguishers.

Unsuitable extinguishing media: Direct water stream may cause frothing, splattering of burning material and spreading of fire.

Specific hazards arising from the chemical: Material may be ignited only if preheated to high temperatures (such in fire conditions). Fire in vicinity poses risk of pressure build-up and rupture. Containers at risk from fire should be cooled with water and, if possible, removed from the danger area. Hazardous combustion products: carbon and nitrogen oxides, amines, hydrogen cyanide, lower molecular weight organic molecules, aluminum oxides.

Special Protective Equipment and Precautions for fire-fighters: Wear NIOSH or OSHA approved self-contained breathing apparatus in positive pressure mode with full face piece and full protective gear. Isolate the scene by removing all persons from the incident area. No action should be taken involving any personal risk or without suitable training. Spilled product will cause very slippery walking surfaces.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Keep unnecessary and unprotected personnel from entering. Ensure adequate ventilation/exhaust extraction. Avoid breathing vapors or mist during clean up. Use protective equipment as described in Section 8. Do not touch or walk through spilled material; spilled material may cause a slipping hazard.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Inform the relevant authorities if the product has caused environmental pollution. See Section 12 for more details.

Methods and materials for containment and cleaning up: Remove mechanically; cover the remainder with non-combustible absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth). Following absorption, transfer into properly labeled chemical waste containers. If necessary, repeat application of absorbent material until all liquid has been removed from the surface. Wash the spill site with soap and water. Cover container and remove from work to a well-ventilated area. Properly dispose of the waste material and any contaminated equipment (i.e., broom or brush) in accordance with existing federal, state and local regulations. For major spills: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Wash spillages into an effluent treatment plant or contain and collect with an absorbent material as described in the previous paragraph. For minor spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly with soap and water to remove residual contamination. Never return spills to original containers for re-use.

Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, see Section 1 for the Emergency contact; for further disposal measures, see Section 13.

SECTION 7 – HANDLING AND STORAGE

Precautions for safe handling: Protect chemical from atmospheric moisture. Avoid prolonged exposure to heat and air. Keep away from sources of ignition. Do not reseal if contamination is suspected.

Use adequate ventilation to keep airborne levels below the exposure limits. Do not breathe vapors and mists. Wear respiratory protection if material is heated, mixed, sprayed or used in a confined space. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash hands thoroughly after handling. Hands and/or face should be washed before eating, drinking and smoking and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities: Store in original or approved alternative container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink.

Released: July 29, 2016

Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Protect it against physical damage and moisture. Normal temperature and pressures do not affect the material. Keep liquid away from heat, sparks and flame. Do not cut, drill, grind, weld or perform similar operations on or near containers. Use appropriate containment to avoid environmental contamination. Segregate from acids and acid forming substances.

Storage stability: Stable under normal conditions.

Storage temperature: 60 - 90°F (16 – 32°C)

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200. Employees and consumers should be warned of health risks associated with product use. See Section 8 for additional information on hygiene measures.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters/Occupational exposure limit values: Not available for mixture. Results for components are listed in Section 15.

Appropriate engineering controls: Good local and general ventilation should be sufficient to control worker exposure to airborne contaminants below recommended exposure limits. Local exhaust may be required in some areas.

Personal protective equipment:

Eye/face protection:

When directly handling liquid product, eye protection is recommended. Examples of eye protection include safety glasses and goggles or full face shield when there is a greater risk of splash. Contact lenses should not be worn when working with chemicals.

Skin/body protection:

Impervious gloves (nitrile butyl rubber, neoprene and PVC) should be worn always when working with this product. Body should be covered with appropriate clothing (apron, arm covers or full body suit) depending on the task being performed and the risks involved. Protective clothing should be selected and used in accordance with “Guidelines for the Selection of Chemical Protective Clothing” published by ACGIH. Wash contaminated clothing before reuse. Store work clothing separately. Appropriate footwear should be also selected based on the task being performed and the risks involved.

Respiratory protection:

Use local or general ventilation to control exposures below applicable exposure limits. When ventilation is inadequate, use either an atmosphere supplying respirator or NIOSH or OSHA approved air-purifying respirator for organic vapors. Respirator must be properly fitted and its selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Additional Protective Measures: Educate and train employees in safe handling of this product. Follow all label instructions. As a general hygiene practice, wash hands and face after use. Clean water should always be readily available for emergency skin and eye washing. Emergency eyewash fountains and safety shower are recommended in close proximity as a matter of good work practice.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White Liquid
Odor:	Mild
Odor threshold:	Not available
pH:	8 – 10
Melting point/ freezing point:	Not available
Initial boiling point and boiling range:	>200°C
Flash point:	>200°C
Evaporation rate:	Not applicable
Flammability (solid, gas):	Not applicable
Upper/ lower flammability or explosive limits:	Not applicable
Vapor pressure:	Negligible
Vapor density:	Not available
Relative density:	1.00-1.10 @ 25°C (77°F)
Solubility (water):	Very slightly soluble
Partition coefficient n-octanol/water:	Not available
Auto-ignition temperature:	>250°C
Decomposition temperature:	Not available
Viscosity:	Not available

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: Product will not undergo hazardous polymerization. Corrosive effects to metal are not anticipated. Based on its structural properties the product is not classified as oxidizing. Does not form flammable gases in the presence of water.

Released: July 29, 2016

Chemical stability: Stable under recommended storage conditions. Product is hygroscopic; contamination with moisture will negatively affect product performance. Avoid unintended contact with isocyanates; the reaction will generate heat.

Conditions to avoid: Unintentional contact with moisture, excessive heat, open flame and sparks. Avoid mist formation.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Depend upon temperature, air supply and presence of other materials. Can include, but are not limited to carbon and nitrogen oxides, amines, hydrogen cyanide, lower molecular weight organic molecules, aluminum oxides.

SECTION 11 – TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin and Eye Contact, Inhalation and Ingestion.

Symptoms of exposure:

Acute toxicity:

Oral: Not anticipated, however, adverse symptoms may include abdominal pain, nausea and diarrhea.

Dermal: Not anticipated; adverse symptoms are not expected.

Inhalation: Inhalation is unlikely due to the low vapor pressure.

Skin corrosion / irritation:

May cause mild, temporary skin irritation if not washed off accordingly. Adverse symptoms may include redness.

Serious eye damage / eye irritation:

May cause mild, temporary eye irritation. Adverse symptoms may include tearing and redness.

Specific target organ toxicity, single exposure:

Not expected.

Aspiration hazard: Not an aspiration hazard.

Chronic toxicity:

Respiratory and Skin Sensitizer:

This product does not contain components that are reported to be a skin or respiratory sensitizer.

Germ cell mutagenicity:

Risk to humans is not expected from exposure to this product.

Carcinogenicity:

This product contains a component reported to be possibly carcinogenic to humans by IARC.

- Titanium Dioxide, CAS #: 13463-67-7: IARC: Group 2B (Possibly Carcinogenic to Humans)
ACGIH: Not classifiable as human carcinogen
- Zeolites, CAS #: 1318-02-1: IARC: Group 3 (Not Classifiable as to its Carcinogenicity to Humans)

Negative effects of Titanium Dioxide on health are minimized, considering that it is dispersed in liquid. However, precautions should be taken to avoid breathing mists created by heating, mixing or spraying and dust from cutting or grinding of cured product containing this component.

Reproductive toxicity:

Risk to humans is not expected from exposure to this product.

Specific target organ toxicity, repeated exposure:

Kidney, lungs/respiratory system, central nervous system.

Medical conditions aggravated by overexposure:

Kidney, lungs/respiratory system, central nervous system and skin disorders if product is handled without adequate protection.

Toxicity test results: Not available for mixture. Results for components:

Components	Test Results
Natural Oil Based Polyol, CAS #: Trade Secret	Non Hazardous
Glycol, CAS #: Trade Secret	<p><u>Acute Toxicity</u> Oral LD50 (Rat): >5,000 mg/kg; No mortality was observed (OECD Test Guideline 401) Dermal LD50 (Rat): >5,000 mg/kg; No mortality was observed (OECD Test Guideline 402) Inhalation, aerosol, LC50 (Rat), 4hrs: 1-5 mg/L; No mortality was observed (similar to OECD Test Guideline 403) Skin corrosion/irritation (Rabbit): Non-irritating (OECD Test Guideline 404) Serious eye damage/eye irritation (Rabbit): Non-irritating. STOT, SE: risk to humans is not expected from exposure to this product. Aspiration hazard: No.</p> <p><u>Chronic toxicity</u> Sensitization, skin and respiratory: Negative (Guinea pig) Mutagenicity: Not mutagenic in bacteria, mammalian cell culture and test with mammals. Carcinogenicity: Not observed. Reproductive toxicity: Not observed. STOT, RE: Central nervous system, kidney.</p>
Poly ether Polyol, CAS #: Trade Secret	<p><u>Acute Toxicity</u> Oral LD50 (Rat): 2,000-5,000 mg/kg (OECD Test Guideline 401) Dermal LD50 (Rabbit): >2,000 mg/kg (OECD Test Guideline 402) Skin corrosion/irritation (Rabbit): not irritating (OECD Test Guideline 404) Serious eye damage/eye irritation (Rabbit): not irritating (OECD Test Guideline 405)</p> <p><u>Chronic toxicity</u> Skin sensitization (Guinea pig): Non-sensitizing (OECD Test Guideline 406)</p>

<p>Titanium Dioxide, CAS #: 13463-67-7</p>	<p><u>Acute toxicity</u> Oral LD50 (Rat): >5,000 mg/kg; a very insoluble compound. The studies in several species, including man, show neither significant absorption nor tissue storage following ingestion of titanium dioxide. Inhalation LC50 (Rat): >6.82 mg/L Skin corrosion/irritation (Rabbit): Slight or no skin irritation. Not dermally absorbed by humans. Serious eye damage/eye irritation (Rabbit): Slight or no eye irritation. <u>Chronic Toxicity</u> Sensitization (Mouse): Not sensitizing on laboratory animals. Germ cell mutagenicity: Non genotoxic. Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans; No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by NTP, ACGIH and OSHA. Titanium dioxide is a frequently used compound in lung clearance studies, where a biologically inert substance is required, however inhalation of high concentrations of fine or ultrafine titanium dioxide particles has been shown to result in pulmonary inflammation, fibrosis, and lung tumors in rats. The same inhalation effects were not observed in mice and hamsters and may be a rat-specific threshold phenomenon, dependent upon lung overloading at high exposure concentrations and possibly of little relevance to humans. Epidemiological data suggest that there is no carcinogenic effect associated with workplace exposure to titanium dioxide dust. STOT, RE: Inhalation: Lung fibrosis; potential occupational carcinogen</p>
<p>Diethyltoluenediamine (DETA), CAS #: 68479-98-1</p>	<p><u>Acute Toxicity</u> Oral LD50 (Rat): 738 mg/kg (OECD Test Guideline 401) Dermal LD50 (Rat): >2,000 mg/kg (OECD Test Guideline 402) Skin corrosion/irritation (Rabbit): Non-irritating (OECD Test Guideline 404) Eye Irritation (Rabbit): Irritating (US-EPA) <u>Chronic toxicity</u> Skin Sensitization (guinea pig): Negative (intracutaneous test) Germ cell mutagenicity: Positive and negative results were seen in various in Vitro and in Vivo studies. Reproductive toxicity: Oral (Rat, females), Dose: 0, 50, 150, 500 mg/kg General Toxicity Maternal: No observed adverse effect level: 50 mg/kg body weight Teratogenicity: No observed adverse effect level: 500 mg/kg body weight Embryo-fetal toxicity: No observed adverse effect level: 150 mg/kg body weight Embryotoxic effects and adverse effects on the offspring were detected only at high maternally toxic doses (OECD Test Guideline 414) STOT, RE: Oral (Rat), 90 days, Dose: 50-125-320ppm, NOEL: ≥8 mg/kg; LOEL: ≥21 mg/kg; Dermal (Rabbit), 21 day, Dose: 1-10-100mg/kg, NOEL: ≥10 mg/kg Chronic ingestion may cause liver damage. Pancreas damage.</p>
<p>Zeolites, CAS #: 1318-02-1</p>	<p><u>Acute Toxicity</u> Oral LD50 (Rat): >5,110 mg/kg (OECD Guideline 401); May cause gastrointestinal tract irritation. Dermal LD50 (Rabbit): Not data available Inhalation LC50 (Rat)(dust/aerosol), 4hrs : >5.3 mg/L. Slightly irritant. Skin corrosion/irritation (Rabbit): Slightly irritant. May cause dehydration. Serious eye damage/eye irritation (Rabbit): Slightly irritant. May cause abrasion or mechanical irritation. STOT, SE: risk to humans is not expected from exposure to this product. Aspiration hazard: No <u>Chronic toxicity</u> Sensitization, skin and respiratory: Not sensitizer (Guinea pig maximization test) Germ cell mutagenicity: Risk to humans is not expected from exposure to this product. Carcinogenicity: IARC: Group 3 (Not Classifiable as to its Carcinogenicity to Humans) Reproductive toxicity: No adverse effects in rats and rabbits or their offspring following administration in the drinking water during pregnancy. STOT, RE: Effects on kidney were observed in rats and dogs administered high dose levels in their feed for one month. Effect on blood, chronic pneumonitis and acute bronchopneumonia were observed in dogs. Long-term inhalation by rats and dogs produced inflammation in the lungs associated with accumulation of particulate.</p>

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: Not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Do not release into natural waters.

Persistence and degradability: Not readily biodegradable by OECD criteria.

Bioaccumulative potential: No significant accumulation in organisms is expected.

Mobility in soil: Not known.

Other adverse effects: Not known.

Ecotoxicity test results: Not available for the mixture. Results for components:

Components	Test Results
<p>Natural Oil Based Polyol, CAS #: Trade Secret</p>	<p>Non Hazardous</p>
<p>Glycol, CAS #: Trade Secret</p>	<p><u>Aquatic toxicity:</u> High probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. <u>Acute Toxicity:</u> Fish (fathead minnow), 96hrs: LC50: >40,000 mg/L (OECD Test Guideline 203, static). Product not tested; The statement has been derived from substances/products of a similar structure or composition. Aquatic Invertebrates (Daphnia magna), 48hrs: EC50: >100 mg/L (OECD Test Guideline 202, part 1, static) Aquatic Plants (algae), 72hrs: EC50: >100 mg/L (OECD Test Guideline 201) Activated sludge (bacteria), 18hrs: EC10: >1,000 mg/L <u>Chronic toxicity:</u> Other terrestrial, non-mammals, 14days: LD50: >2,000 mg/kg <u>Ecological Data:</u> Biodegradation: Readily biodegradable (OECD Test Guideline 301D) Elimination, aerobic, activated sludge, domestic, 28 days: 80-90% BOD of the ThOD (OECD Test Guideline 301F)</p>

	DOC reduction, aerobic, microorganisms, industrial, 64days: 20-25 % (OECD Test Guideline 306) Bioaccumulative potential: Does not significantly accumulate in organisms. Mobility in soil: Not expected.
Poly ether Poly ol, CAS #: Trade Secret	<u>Acute Toxicity</u> Fish: LC50 (fathead minnow), 96hrs: 1,000 mg/L Aquatic invertebrates: EC50 (Daphnia magna), 24hrs: >1,000 mg/L Aquatic plants: EC50 (green algae), 96hrs: 500-1,000 mg/L <u>Ecological Data</u> Toxicity to microorganisms: DEV-L2: >1,000mg/L Activated sludge, aerobic, domestic EC20, 30min: 1,000 mg/L (OECD Guideline 209) Biodegradability: poorly biodegradable Elimination information (aerobic, predominantly domestic sewage): 9 % BOD of the ThOD (28 d) (OECD Guideline 301F) Stability in water: in contact with water the substance will hydrolyze slowly. Bioaccumulative potential: not expected based on octanol/water distribution coefficient (log Pow). Mobility in soil: No data available.
Titanium Dioxide, CAS #: 13463-67-7	<u>Aquatic toxicity</u> : Fish LC0 (orfe, freshwater fish), 48h: >1,000 mg/L. <u>Ecological Data</u> : Persistence and degradability: Methods for the determination of biodegradability are not applicable to inorganic substances. Bioaccumulative potential: The product is practically insoluble in water and not biodegradable. Mobility in soil: No data available. PBT and vPvB assessment is not required for inorganic substances. Titanium dioxide is a stable compound that is insoluble in water and therefore would not be expected to be present in drinking water. Based on the lack of absorption as well as no identified toxicological effects of concern in animal testing, there are also no risk concerns for non-target terrestrial organisms resulting from the use of titanium dioxide as an inert ingredient.
Diethyltoluenediamine (DETA), CAS #: 68479-98-1	<u>Aquatic toxicity</u> : Very toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment. <u>Acute Toxicity</u> Fish: LC50 (Fathead minnow), 96hrs: >106 mg/L (OECD Guideline 203) Aquatic Invertebrates: EC50 (Daphnia magna), 48hrs: 5.8 mg/L (OECD Guideline 202) Algae:ErC50 (Green algae), 72hrs: 104 mg/L (OECD Guideline 201) <u>Ecological Data</u> Microorganisms, EC50 (bacterium), 24hrs: >170 mg/L (DIN 38412 Part 8) Biodegradation, 28days: <1 % (OECD Guideline 301D); COD: 2,370 mg/g
Zeolites, CAS #: 1318-02-1	<u>Acute Toxicity</u> : Fish (fathead minnow), 96hrs: LC50: >680 mg/L (EPA 72-1, static). The details of the toxic effect relate to the nominal concentration. The LC50 is higher than the solubility limit. Aquatic invertebrates (Daphnia magna), 24hrs: EC50: 2,808 mg/L (OECD Test Guideline 202, part 1, static) Aquatic plants (Green algae), 96hrs: EC50: >328 mg/L (OECD Test Guideline 201, static). The details of the toxic effect relate to the nominal concentration. Tested above maximum solubility. The product has low solubility in the test medium. An eluate has been tested. Microorganisms (Bacteria), 16hrs: EC50: 950 mg/L (Growth inhibition) (DIN 38412, Part 8). The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An eluate has been tested. <u>Chronic toxicity</u> : Fish (fathead minnow), 30days: NOEC: ≥86.7 mg/L (OPP 72-5, EPA-Guideline, Flow through). The statement of the toxic effect relates to the analytically determined concentration. Aquatic invertebrates (Daphnia magna), 21days: NOEC: 32 mg/L (OECD Test Guideline 211, semistatic). The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An eluate has been tested. <u>Ecological Data</u> : Biodegradability: Not readily biodegradable. The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants. It cannot be eliminated from water by biological purification processes. Mobility in soil: Transport between environmental compartments: Study scientifically not justified.

SECTION 13 – DISPOSAL CONSIDERATIONS

Product Disposal: The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

Container disposal: Even after emptying, container may retain residues. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation. This material and its container must be disposed of in a safe way.

SECTION 14 – TRANSPORT INFORMATION

Land transport, U.S. DOT: Non-regulated
Sea transport, IMDG: Non-regulated
Air transport, IATA/CAO: Non-regulated

SECTION 15 – REGULATORY INFORMATION

U.S. Regulations:

OSHA HCS: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29CFR 1910.1200.

TSCA Regulations:

All components of this product are listed or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

EPCRA Section 302 (40 CFR Part 355) (Emergency Response Planning, Extremely Hazardous Substance):

No components are subject to the reporting.

EPCRA Section 304 (40 CFR Part 355) (Emergency Release Notification Requirements):

No components are subject to the reporting.

EPCRA Sections 311 & 312 (Hazardous Chemical Inventory Reporting, Hazard Categories):

Acute Health Hazard, Chronic Health Hazard

EPCRA Section 313 (40 CFR Part 372) (Toxic Chemical Release Inventory Reporting):

No components are subject to the reporting.

CERCLA Sections 102-103 (40 CFR Part 302) (Hazardous Substances Release Notification):

No components are subject to the reporting.

Clean Air Act:

- Ozone Depleting Substances (ODS): This product does not contain and is not manufactured with ozone depleting substances.
- Hazardous Air Pollutants, OSHA, Section 112(b), Table Z-1: The following components are listed:

Substance		Regulatory Limits			Recommended Limits	
		OSHA PEL	Cal/OSHA PEL	NIOSH REL	ACGIH® 2015 TLV®	
		ppm	mg/m ³	8-hour TWA, mg/m ³	Up to 10-hour TWA, mg/m ³	8-hour TWA, mg/m ³
Titanium Dioxide, CAS #: 13463-67-7	Total dust	-	15	10 (as PNOR)	2.4 mg/m ³ (fine) 0.3 mg/m ³ (ultrafine), Ca See Appendix A & C	10
Hydrated Aluminum Silicate (Kaolin), CAS #: 1332-58-7	Total dust	-	15	-	10	-
	Respirable fraction	-	5	2 *	5	2 *
Aluminum Oxide, CAS #: 1344-28-1	Total dust	-	15	10	-	-
	Respirable fraction	-	5	5	-	-

ppm-parts per million; *- no asbestos and <1% Crystalline Silica; Ca - Potential occupational carcinogens; Appendix A, C and D refers to Appendixes of HAP List, Section 112(b) of Clean Air Act

NIOSH IDLH: Titanium dioxide, CAS #: 13463-67-7: 5,000 mg/m³, Ca

Clean Water Act:

- Section 311(b): No components are subject to the reporting.

NFPA rating: Health: 2 Fire: 1 Reactivity: 1 Special: 0

HMIS rating: Health: 2* Flammability: 1 Physical hazard: 1

State Regulations:

California Prop. 65 Components:

This product contains chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

- Titanium dioxide (airborne, unbound particles of respirable size), CAS #: 13463-67-7
 - causes cancer; Date listed: September 2, 2011

Instruction: for regulatory information on components of this mixture, check the appropriate state websites.

International Regulations/Inventories:

Canada: All ingredients of this product are listed or are exempt from the DSL.

WHMIS Classification (Controlled Products Regulations): Class D2B: Material causing other toxic effects

WHMIS Label Information:



SECTION 16 – OTHER INFORMATION

LEGEND

GHS	Globally Harmonized System
CAS	Chemical Abstracts Services
EC	European Community
EPA	Environmental Protection Agency
OSHA	Occupational Safety and Health Administration
ACGIH	American Conference of Governmental Industrial Hygienists
NIOSH	National Institute of Occupational Safety and Health
PEL	Permissible Exposure Limits
TLV	Threshold Limit Value
REL	Recommended Exposure Limit
TWA	Time-Weighted Average
STEL	Short-term exposure limit
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
COD / BOD	Chemical Oxygen Demand / Biological Oxygen Demand
STOT, SE	Specific Target Organ Toxicity following Single Exposure
STOT, RE	Specific Target Organ Toxicity following Repeated Exposure
DOT	Department of Transportation
IMDG	International maritime dangerous goods code
IATA, ICAO	International Air Transport Association, International Civil Aviation Organization
TSCA	Toxic Substances Control Act
EPCRA	Emergency Planning and Community Right-to-Know Act
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
CFR	Code of Federal Regulations
RQ	Reportable Quantity
EHS	Extremely Hazardous Substances
DSL	Domestic Substance List
WHMIS	Workplace Hazardous Materials Information System

Latest revision date: July 29, 2016

Date of the previous revision: November 17, 2015 – Preparation of SDS in accordance to the GHS requirements

Disclaimer: The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Rhino Linings Corporation makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.