



ISO 9001:2008  
FM62236

## E-XP2 R2

<b>Output:</b>	20 lbs/min (2.0 gal/min, 7.6 liter/min)
<b>Output per Cycle (A&amp;B):</b>	.0203 gal (.0771 liter)
<b>Max Operating Pressure:</b>	3500 psi (241 bar)
<b>Electrical:</b>	230 V; 3 phase delta; 62 amp 230 V; 1 phase; 100 amp 400 V; 3 phase wye; 35 amp
<b>Primary Heaters:</b>	15,300 watts
<b>Weight:</b>	355 lbs (159 kg)
<b>Dimensions:</b>	63" H x 26.3" W x 15" D (16 x 6.68 x 3.81 m)
<b>Heated Hoses:</b>	50 ft 1/4" x 1/4" with 10 ft whip 1/4" x 1/4" (15 m x 6 mm x 6 mm with 3 m whip, 6 mm x 6 mm)
<b>Max Hose Length:</b>	310 ft (94 m)



### E-XP2 R2 ELITE

Specifications similar to the standard model and also includes:

- Graco InSite Remote Reporting Technology
- Inlet Pressure and Temperature Sensor (interfaces with Graco InSite)

With a maximum operating pressure of 3500 PSI and a max hose length of 310 feet, there's nothing the E-XP2 R2 can't do. The additional hose length lets you get closer to the job and gives you the option to spray most Rhino Linings® protective foam and linings systems. The E-XP2 R2 is perfect for the following applications:

- Commercial Roofs
- Concrete Protection
- Foam Encapsulation
- Large Vehicle Roofs
- Marine Applications
- OEM Protection
- Pipe and Tank Coatings
- Primary Containment
- Truck Bed Liners (3 or more a day)



## E-XP1

<b>Output:</b>	10 lbs/min (1.06 gal/min, 3.8 liter/min)	<b>Weight:</b>	342 lbs (155 kg)
<b>Output per Cycle (A&amp;B):</b>	.0104 gal (.0395 liter)	<b>Dimensions:</b>	46" H x 31" W x 33" D
<b>Max Operating Pressure:</b>	2500 psi (172 bar)	<b>Heated Hoses:</b>	50 ft 1/4" x 1/4" with 10 ft whip 1/4" x 1/4" (15 m x 6 mm x 6 mm with 3 m whip, 6 mm x 6 mm)
<b>Electrical:</b>	230 V; 3 phase; 43 amp 230 V; 1 phase; 69 amp 400 V; 3 phase; 24 amp	<b>Max Hose Length:</b>	210 ft (64 m)
<b>Primary Heaters:</b>	10,200 watts		

Recommended for numerous vehicle protection and mobile applications, the E-XP1 is the high performance plural component spray machine that can process Rhino Linings protective foam and lining systems. The E-XP1 is one of the most universal pieces of equipment in the elastomer and spray foam industry, which makes it the perfect machine for a variety of coating applications that include:

- Concrete Protection
- Containment Areas
- Heavy Duty Flooring
- Military Equipment
- Mining and Construction
- Props and Scenery
- Specialty Vehicles
- Tank Linings
- Truck Bed Liners (3 or more a day)

# Rhino™ Spray Equipment



## E-10hp

<b>Output:</b>	1 gpm (3.8 lpm)	<b>Dimensions:</b>	46" H x 29" W x 36" D (11.7 x 7.3 m x 9.1 m)
<b>Max Operating Pressure:</b>	3000 psi (206 bar)	<b>Tank Capacity:</b>	6 gal (22.7 l)
<b>Electrical:</b>	230 V; 1 phase; (2) 20 amp 120V; 1 phase; (2) 15 amp	<b>Heated Hoses:</b>	35 ft (10 m) insulated bundle of five
<b>Primary Heaters:</b>	2,760 watts (230 V) 2,000 watts (120 V)	<b>Max Hose Length:</b>	105 ft (32 m)
<b>Weight:</b>	239 lbs (108 kg)		

The E-10hp, Graco's answer to compact and portable, is recommended for spraying up to two truck beds per day and small applications up to 1000 square feet. Compared to the E-10, the E-10hp has 50% more power, faster material heating and improved spray performance with reduced pressure drop. Providing accurate tank temperature readings with gauges in the Y-strainers, the E-10hp also has wide tank openings for easy cleaning and material loading. The E-10hp is perfect for a variety of coatings projects that include:

- Below-grade Foundation Waterproofing
- Marine Applications
- Truck Bed Liners (up to 2 a day)
- Foam Insulation
- Specialty Vehicles
- Wheel Wells and Rocker Panels
- Heavy Duty Flooring
- Trailers/Sea Containers

## Rhino™ LP-21



<b>Output (Variable):</b>	0.3 to 5 lbs/min (0.1 to 2.3 kgs/min)
<b>Max Operating Pressure:</b>	350 psi
<b>Electrical:</b>	(with a $\leq$ hp variable speed motor) 120 vac 1 ph, 20 amp 240 vac 1ph, 10 amp
<b>Dimensions:</b>	12" H x 6" W x 24" L (30 cm x 15 cm x 61 cm)
<b>Hoses:</b>	50 to 100 ft max (15 to 30 m) low pressure moisture lock
<b>Weight:</b>	50 lbs (22.7 kg)

The Rhino LP-21, our entry level piece of equipment that has the ability to spray Rhino Linings® 2:1 ratio urethane products. The low pressure machine has been engineered for ease of operation, safety and predictable performance. At the heart of this system is the LP-21 proportioning unit that delivers precisely metered chemicals at a variable flow rate for consistent results. The Rhino LP-21 is recommended for a variety of smaller coatings projects that include:

- Audio Speaker Boxes
- RV and Service Body Compartments
- Cooling Tower Pans
- Truck Accessory Parts
- Motor Home and Bus Steps
- Truck Bed Liners (1 – 2 per week)
- Roof Repairs