



StoneCrete™ Release Oil Data Sheet

Part # RO

DESCRIPTION: Concrete Solutions® StoneCrete™ Release Oil is a concentrated oil that is mixed with 100% mineral spirits to create a StoneCrete™ tile mold release agent. The mix is sprayed or wiped into StoneCrete™ tile molds before adding StoneCrete™ tile admix to make it easier to remove tiles once they have dried.

FEATURES & BENEFITS:

- Facilitates the easy removal of StoneCrete tiles from StoneCrete tile molds.
- Concentrated for extended use
- Can be applied with a trigger nozzle sprayer

CHEMICAL PROPERTIES:

Coverage Rate per mixed gallon
Color

Result

1000 sqft
clear

MIXING INSTRUCTIONS:

Mix 4 oz of Release Oil with 1 gallon of 100% mineral spirits. Never use Release Oil on StoneCrete tile molds without diluting with mineral spirits first.

APPLICATION INSTRUCTIONS:

Rub a small amount of mixed Release Oil on each StoneCrete tile mold using a cotton rag or grout sponge. For easier application you may also use a trigger nozzle sprayer to apply a fine mist over the mold. Apply Release Oil wait approximately 10-15 minutes to allow the Release Oil to dry prior to pouring StoneCrete Tile Admix into the mold. The tiles will be easiest to remove after approximately 10 hours. Do not leave tiles in the molds for more than 24 hours.

COLOR: Clear

HOW SUPPLIED: 8 oz Bottle

WARNING: When combined with mineral spirits, Release Oil is combustible and should be kept away from open flames. Turn out all pilot lights. Wear the proper breathing mask in areas with poor ventilation. Read Material Safety Data Sheet before using. For professional use only!

SAFETY PRECAUTIONS: Health Considerations: Consult the Rhino Linings® Safety Data Sheets (SDS)

Chemical systems require the use of proper safety equipment and procedures. Please follow the Rhino Linings® product SDS and Safety Manual for detailed information and handling guidelines.

For Your Protection: The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning the products and their uses, applications, storage and handling are only the opinion of Rhino Linings Corporation. Users should conduct their own tests to determine the suitability of these products for their own particular purposes and of the storage and handling methods herein suggested. The toxicity and risk characteristics of products made by Rhino Linings Corporation will necessarily differ from the toxicity and risk characteristics developed when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors.

Because of numerous factors affecting results, **Rhino Linings Corporation makes no warranty of any kind, express or implied**, other than that the material conforms to its applicable current Standard Specifications. Rhino Linings Corporation hereby disclaims any and all other warranties, including but not limited to those of merchantability or fitness for a particular purpose. No statements made herein may be construed as a representation or warranty. The liability of Rhino Linings Corporation for any claims arising from or sounding in breach of warranty, negligence, strict liability, or otherwise shall be limited to the purchase price of the material.

©2017 Rhino Linings Corporation. All rights reserved.

www.concretesolutions.com



Rhino Linings Corporation

9747 Businesspark Avenue, San Diego, CA 92131
858-450-0441 • Fax 858-450-6881
1-800-422-2603
www.rhinolinings.com

Concrete Solutions by Rhino Linings

7455 Carroll Road, San Diego, CA 92121
1-800-232-8311 • Fax 858-566-4346
www.concretesolutions.com